

PH-100 Series Dome Housing

Keeps your Compro PTZ network cameras out of harm's way



* Camera not included

- Designed for Compro IP5X0 and NC5X0 PTZ network cameras
- 5" high-clarity bubble
- Fireproof housing material
- Indoor ceiling installations
- 330° pan range and 110° tilt range
- Easy installation

Expressly designed for Compro PTZ cameras, the PH-100 series dome housing features a 5-inch smoked or clear bubble and a mechanical design that allows for easy camera installation and cabling.

The PH-100 series dome housings consist of PH100T (with clear bubble) and PH-100S (with smoked bubble). The dome housing is made of fireproof material where as the dome top is formed from high-clarity polycarbonate plastic.

The internal dimensions of this dome housing are designed to accommodate a Compro PTZ network camera with or without a Compro USB wireless adapter attached. The housing also allows for easy cabling and connection to the camera with a detachable connector shield.

Courtesy of the inherent strength and optical clarity of the polycarbonate material, the dome housing is capable of providing Compro PTZ cameras with effective protection without compromising image quality or sacrificing wireless connection.

This dome housing is suitable for indoor applications. The PH-100S dome housing available with a smoked bubble can help conceal camera position and address the privacy concern.

Furthermore, the ceiling bracket included in the package is easy to install in a hard-ceiling or a suspended ceiling. The PH-100 series dome housing with its 5-inch dome top also allows Compro PTZ cameras to pan and tilt freely inside the housing, enabling users to take the full advantage of the installation. In addition, the innovative bracket design makes it fast and easy to mount and unmount the dome housing.

In summary, the PH-100 series dome housing equipped with a unique feature set is the best companion for your Compro PTZ cameras.



HARDWARE SPECIFICATIONS

GENERAL

Models	• PH-100T (Transparent bubble) • PH-100S (Smoked bubble)
Construction	
Bubble	PC (IK10)
Housing	PC + ABS (Fireproof material: 94V0)
Ceiling Bracket	Steel
Housing Bracket	Steel
Dimensions	Ø189mm x 154.1mm(H)
Unit Weight	0.53 kg / 1.16 lb (camera not included)
Shipping Weight	0.76 kg / 1.67 lb (camera not included)
Package Contents	• Dome housing • Ceiling bracket • Housing bracket • Connector shield • Screw pack • Installation guide

PTZ

Pan Range	330°
Tilt Range	110°

ENVIRONMENTAL

Environment	Indoor
Operating Temperature	10°C~+40°C (50°F~+104°F)
Storage Temperature	0°C~+50°C (32°F~+122°F)

Dimensions

